

ACTUATOR APPLICATION DATA FORM



(03) 9308 0055

(02) 9616 0066

(07) 3717 4452

(08) 8260 7615

CUSTOMER DETAILS

VICTORIA - TASMANIA

SOUTH AUSTRALIA - NT

NEW SOUTH WALES

QUEENSLAND

NAME:			CONTACT:	
ADDRESS:			PHONE:	
DATE:			FAX:	
Application requir	ements			
Quantity required		Stroke (mm)	
load (N)		-	,	
tatic		Tens	ion	Compression
Dynamic	ic		ion	Compression
Linear speed (mm/min)	:	-		
Duty cycle profile: (eg: e:	xtend, dwell 1min,	retract, dwell 1 min, 20 cyc	les per hr, 16hrs per	day, 300 days per year)
Running Synchronized		Running Paral	lel	Running Independently
Electrical				
Motor Voltage	12V	24V	240V	Other
Limit Switches	Fixed	Encoder	Potentior	meter Adj
Controller Required	Yes	☐ No		
Controller Voltage	☐ 12V	24V	240V	Other
IP Rating Required				
Drawing attached & Ap	plication Detail	s Yes 🗌	No 🗌	
The onus is on the user Pay particular attention	full installation in r / installer to ens i to: ide load / mome levice you are mo lounting is impor	sure correct installation. nt load forces being appoving is fully guided other	olied to the actuato er than solely by the nent of the mounts	
Other Comments:				
NATIONAL LINEAR DEP	ARTMENT (WA)	linear@statewi	debearings.com.a	u (08) 9475 5000

linearvic@statewidebearings.com.au

linearsa@statewidebearings.com.au

linearnsw@statewidebearings.com.au linearqld@statewidebearings.com.au