

BALL SCREW APPLICATION DATA FORM



CUSTOMER DETAILS

NAME:			CONTACT:		
ADDRESS:			PHONE:		
DATE:			FAX:		
System Specification	ons				
Application Orientation:	☐ Vertical	□ Но	rizontal		
Quantity	Screw	☐ Nu	t		
Stroke Length (mm):	Total Length (mm):				
Support Method:	Fixed-Support	ed Fix	ed-Fixed	Fixed-Free	
Load Specification	s				
Axial Load: (kg)	Nominal Stroke Length: (mm)				
System Mass: (kg) _					
Accuracy Specifica	tions				
Axial Play: (mm)		Max Linear	Volocity: (mm/s)		
Load Error: (mm)	Max Acceleration: (mm/s²)				
Repeatability: (mm) _					
Environmental Spe	cifications				
Operating Temperature F	Range:°C		°C		
Shock Loads:	☐ None] Mild	Moderate	Severe	
Vibrations:	☐ None	Mild	Moderate	Severe	
Contamination:					
Drawing attached?	Yes] No			
Comments:					

NATIONAL LINEAR DEPARTMENT(WA)
VICTORIA - TASMANIA
NEW SOUTH WALES
QUEENSLAND
SOUTH AUSTRALIA

linear@statewidebearings.com.au linearvic@statewidebearings.com.au linearnsw@statewidebearings.com.au linearqld@statewidebearings.com.au linearsa@statewidebearings.com.au

(08) 9475 5000 (03) 9755 6044

(02) 9616 0066

(07) 3717 4452 (08) 8260 7615