Issue date: 06-01-2017 Revision date: 10-10-2017 Supersedes date: 06-01-2017 Version number: 2.0



SAFETY DATA SHEET

1. Identification

Product identifier Termalene Electric Motor Bearing Grease

Product Code 301764

Other means of identification

Synonyms Old Product Code 72200; For Package Codes 301764XXXXXX

Product Code 301764

Recommended use of the chemical and restrictions on use

Restrictions on use Lubricant Not available.

Details of manufacturer or importer

Manufacturer

Calumet Branded Products, LLC

GPO Darling Park Towers 2 201 Sussex St. Sydney AU NSW 2000 Australia

2780 Waterfront Pkwy E. Dr., Suite 200 Indianapolis, IN 46214

1 317 328 5660

CHEMTREC: 1800 069 100 (AUS)

2. Hazard(s) identification

Classification of the hazardous chemical

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.

Label elements, including precautionary statements

Hazard symbol(s) None.
Signal word None.

Hazard statement(s) The mixture does not meet the criteria for classification.

Precautionary statement(s)

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Other hazards which do not

result in classification

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixture

Identity of chemical ingredients	CAS number and other unique identifiers	Concentration of ingredients
Distillates (petroleum), Hydrotreated Heavy Naphthenic	64742-52-5	0 - < 100
Distillates (petroleum), Hydrotreated Light Naphthenic	64742-53-6	0 - < 100
Other components below reportable levels		70 - < 80

301764 Version #: 2.0 Revision date: 10-10-2017 Print date: 10-10-2017

Material name: Termalene Electric Motor Bearing Grease SDS AUSTRALIA

4. First-aid measures

Description of necessary first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Personal protection for first-aid responders

Not available.

Symptoms caused by

Irritation of eyes and mucous membranes. Skin irritation.

exposure

Medical attention and special Treat symptomatically.

treatment

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

Water fog. Foam. Dry powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

media

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for fire

fighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Wear

suitable protective equipment.

Hazchem code None.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate

protective clothing. For personal protection, see section 8 of the SDS.

For emergency responders

Not available.

Environmental precautions

Methods and materials for containment and cleaning up Avoid discharge into drains, water courses or onto the ground.

Use water spray to reduce vapors or divert vapor cloud drift. This product is miscible in water. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Precautions for safe handling

Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls and personal protection

Control parameters Follow standard monitoring procedures.

Material name: Termalene Electric Motor Bearing Grease SDS AUSTRALIA

Occupational exposure limits

Australia. National W	orkplace OELs (Workplace Exposure S	Standards for Airborne Contaminan	ts, Appendix A)
Components	Type	Value	

Components	Туре	Value	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	
Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	

Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)

Components	Туре	Value	Form	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Mist.	
Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.	
VCCIH				

ACGIH			
Components	Туре	Value	Form
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable Fraction.
Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelinesOccupational Exposure Limits are not relevant to the current physical form of the product.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, for example personal protective equipment (PPE)

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance

Physical state
Form
Liquid. Paste.
Color
Not available.
Odor threshold
Not available.

Material name: Termalene Electric Motor Bearing Grease
301764 Version #: 2.0 Revision date: 10-10-2017 Print date: 10-10-2017

pH Not available.Melting point/freezing point Not available.

Initial boiling point and

boiling range

680 °F (360 °C) estimated

Flash point 302.0 °F (150.0 °C) Pensky-Martens Closed Cup

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure 0.00001 hPa estimated

Density866.00 kg/m³Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Negligible
Solubility (other) Oil

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperature 500 °F (260 °C) estimated

Decomposition temperatureNot available.Viscosity85 cSt (Base Oil)Viscosity temperature104 °F (40 °C)

Other physical and chemical parameters

Dropping point> 500 °F (> 260 °C)Explosive propertiesNot explosive.Flash point classCombustible IIIBOxidizing propertiesNot oxidizing.

Specific gravity 0.87 VOC < 1%

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on possible routes of exposure

InhalationNo adverse effects due to inhalation are expected.Skin contactNo adverse effects due to skin contact are expected.Eye contactDirect contact with eyes may cause temporary irritation.

Material name: Termalene Electric Motor Bearing Grease
301764 Version #: 2.0 Revision date: 10-10-2017 Print date: 10-10-2017

Ingestion Expected to be a low ingestion hazard.

Symptoms related to

exposure

Irritation of eyes and mucous membranes. Skin irritation.

Not available. **Acute toxicity**

Due to partial or complete lack of data the classification is not possible. Skin corrosion/irritation

Serious eye damage/irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Due to lack of data the classification is not possible.

ACGIH Carcinogens

Distillates (petroleum), Hydrotreated Heavy Naphthenic A4 Not classifiable as a human carcinogen.

MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, PURE, HIGHLY AND SEVERELY REFINED, INHALABLE

FRACTION (CAS 64742-52-5)

Distillates (petroleum), Hydrotreated Light Naphthenic MINERAL OIL, EXCLUDING METAL WORKING FLUIDS,

PURE, HIGHLY AND SEVERELY REFINED, INHALABLE

FRACTION (CAS 64742-53-6)

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ

toxicity - repeated

exposure

Due to lack of data the classification is not possible.

Aspiration hazard Not an aspiration hazard.

Other information This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

A4 Not classifiable as a human carcinogen.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil This product is miscible in water.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal methods Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions)

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

ADG

Not regulated as dangerous goods.

RID

Not regulated as dangerous goods.

Material name: Termalene Electric Motor Bearing Grease SDS AUSTRALIA

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

Safety, health and environmental regulations

National regulations This Safety Data Sheet was prepared in accordance with Australia Model Code of Practice for the

preparation of Safety Data Sheets for Hazardous Chemicals (23/12/2011).

Australia Medicines & Poisons Appendix E

Distillates (petroleum), Hydrotreated Light Naphthenic

(CAS 64742-53-6)

For advice, contact a Poisons information Centre (Phone eg Australia 131 - 126; New Zealand 03 - 4747 - 000) or a doctor (at

once)., If swallowed, do NOT induce vomiting.

Australia Medicines & Poisons Schedule 5

Distillates (petroleum), Hydrotreated Light Naphthenic

(CAS 64742-53-6)

applies to all preparations in any concentration Exception may apply, see the regulation for relevance.

High Volume Industrial Chemicals (HVIC)

Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)

1000 - 9999 TONNES See the regulation for additional information.

International regulations

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

United States & Puerto Rico

 Issue date
 06-01-2017

 Revision date
 10-10-2017

DisclaimerCalumet Branded Products, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is

the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in

the sheet was written based on the best knowledge and experience currently available.

Revision information Product and Company Identification: Synonyms

Material name: Termalene Electric Motor Bearing Grease SDS AUSTRALIA

Yes