Issue date: 12-01-2017 Revision date: 06-28-2018 Supersedes date: 12-04-2017

Version number: 3.0



SAFETY DATA SHEET

1. Identification

Product identifier Anti-Wear Lubricant 150

Product Code 301047 SDS number 6773

Other means of identification

Synonyms Old Product Code 56060; For Package Codes 301047XXXXXX

Product Code 301047

Recommended use of the chemical and restrictions on use

Restrictions on use Not available.

Not available.

Not available.

Details of manufacturer or importer

Manufacturer

Calumet Branded Products, LLC

GPO Darling Park Towers 2 201 Sussex St. Sydney AU NSW 2000 Australia

2780 Waterfront Pkwy E. Dr., Suite 200 Indianapolis, IN 46214

1 317 328 5660

CHEMTREC: 1800 069 100 (AUS)

2. Hazard(s) identification

Classification of the hazardous chemical

Physical hazards Not classified.

Health hazardsCarcinogenicityCategory 1BEnvironmental hazardsHazardous to the aquatic environment, acuteCategory 2

hazard

Label elements, including precautionary statements

Hazard symbol(s) None.
Signal word None.

Hazard statement(s) Toxic to aquatic life.

Precautionary statement(s)

Prevention Avoid release to the environment.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards which do not

result in classification

None known.

Supplemental information 45.63% of the mixture consists of component(s) of unknown acute hazards to the aquatic

environment.

3. Composition/information on ingredients

Mixture

Identity of chemical ingredients	CAS number and other unique identifiers	Concentration of ingredients
PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED HEAVY	64742-70-7	30 - < 40
Other components below reportable levels		60 - < 70

Material name: Anti-Wear Lubricant 150 SDS AUSTRALIA

301047 Version #: 3.0 Revision date: 06-28-2018 Print date: 06-28-2018

4. First-aid measures

Description of necessary first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Treat symptomatically.

Personal protection for first-aid responders

Not available.

Symptoms caused by

Irritation of eyes and mucous membranes. Skin irritation.

exposure

Medical attention and special treatment

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

Water fog. Foam. Dry powder. Carbon dioxide (CO2).

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

media

media

During fire, gases hazardous to health may be formed.

Special protective equipment

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Wear

suitable protective equipment.

and precautions for fire fighters

Hazchem code

None.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure

adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

For emergency responders

Not available.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into

drains, water courses or onto the ground.

remove residual contamination.

Methods and materials for containment and cleaning up Use water spray to reduce vapors or divert vapor cloud drift. This product is miscible in water.

Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Precautions for safe handling

Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Material name: Anti-Wear Lubricant 150

301047 Version #: 3.0 Revision date: 06-28-2018 Print date: 06-28-2018

2/6

8. Exposure controls and personal protection

Control parameters Follow standard monitoring procedures.

Occupational exposure limits

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)

Components Type Value

PARAFFIN OILS TWA 5 mg/m3

(PETROLEUM), CATALYTIC DEWAXED HEAVY (CAS

64742-70-7)

Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational

Environment)

ComponentsTypeValueFormPARAFFIN OILSTWA5 mg/m3Mist.

(PETROLEUM), CATALYTIC DEWAXED HEAVY (CAS

64742-70-7)

US. ACGIH Threshold Limit Values

 Components
 Type
 Value
 Form

 PARAFFIN OILS
 TWA
 5 mg/m3
 Inhalable fraction.

(PETROLEUM), CATALYTIC DEWAXED HEAVY (CAS 64742-70-7)

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, for example personal protective equipment (PPE)

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance

Physical state
Form
Liquid.
Color
Not available.
Odor
Not available.
Odor threshold
Not available.
PH
Not available.
Melting point/freezing point
Not available.

Initial boiling point and

boiling range

> 615.2 °F (> 324 °C)

Flash point 420.8 °F (216.0 °C) Pensky-Martens Closed Cup

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Material name: Anti-Wear Lubricant 150 SDS AUSTRALIA

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Not available. Flammability limit -

upper (%)

Explosive limit - lower

(%)

Explosive limit - upper

(%)

Not available.

Not available.

Not available. Vapor pressure Density 886.00 kg/m3 Not available. Vapor density Relative density Not available.

Solubility(ies)

Solubility (water) Negligible Solubility (other) Oil

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 500 °F (260 °C) estimated

Decomposition temperature Not available.

Viscosity 150 cSt ASTM D445 Viscosity temperature 104 °F (40 °C)

Other physical and chemical parameters

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

Specific gravity 0.89 VOC 0 %

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

At thermal decomposition temperatures, carbon monoxide and carbon dioxide.

11. Toxicological information

Information on possible routes of exposure

Inhalation No adverse effects due to inhalation are expected. Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to

exposure

Irritation of eyes and mucous membranes. Skin irritation.

Material name: Anti-Wear Lubricant 150

301047 Version #: 3.0 Revision date: 06-28-2018 Print date: 06-28-2018

4/6

Product Species Test Results

Anti-Wear Lubricant 150

Acute Oral

LD50 Rat 2003 mg/kg estimated

Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible.

Serious eye damage/irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Due to lack of data the classification is not possible.

ACGIH Carcinogens

MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, A2 Suspected human carcinogen.

POORLY AND MILDLY REFINED (CAS 64742-70-7)

PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED A4 Not classifiable as a human carcinogen.

HEAVY MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, PURE, HIGHLY AND SEVERELY REFINED,

INHALABLE FRACTION (CAS 64742-70-7)

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity - repeated

Due to lack of data the classification is not possible.

Assiration barara

exposure

Aspiration hazard Not an aspiration hazard.

12. Ecological information

Ecotoxicity Toxic to aquatic life.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil This product is miscible in water.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal methodsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and

its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

ADG

Not regulated as dangerous goods.

Material name: Anti-Wear Lubricant 150 SDS AUSTRALIA

^{*} Estimates for product may be based on additional component data not shown.

RID

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

Safety, health and environmental regulations

National regulations This Safety Data Sheet was prepared in accordance with Australia Model Code of Practice for the

preparation of Safety Data Sheets for Hazardous Chemicals (23/12/2011).

International regulations

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 12-01-2017 **Revision date** 06-28-2018

Disclaimer Calumet Branded Products, LLC cannot anticipate all conditions under which this information and its

> product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in

the sheet was written based on the best knowledge and experience currently available

SDS AUSTRALIA