



SAFETY DATA SHEET

1. Identification

Product identifier No-Tox Food Grade Silicone Lubricant
Product Code 300879
Other means of identification
Synonyms Old product Code 61780; For Package Codes 300879XXXXXX
Product Code 300879
Recommended use of the chemical and restrictions on use
Recommended use Lubricant
Restrictions on use Not available.

Details of manufacturer or importer

Manufacturer

Calumet Branded Products, LLC
GPO Darling Park Towers 2 201 Sussex St. Sydney AU NSW 2000 Australia
2780 Waterfront Pkwy E. Dr., Suite 200 Indianapolis, IN 46214
1 317 328 5660
CHEMTREC: 1800 069 100 (AUS)

2. Hazard(s) identification

Classification of the hazardous chemical

Physical hazards	Flammable aerosols	Category 1
Health hazards	Skin corrosion/irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1

Label elements, including precautionary statements

Hazard symbol(s)



Signal word

Danger

Hazard statement(s)

Extremely flammable aerosol. Causes skin irritation. May cause drowsiness or dizziness. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)

Prevention

Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves.

Response

If medical advice is needed, have product container or label at hand. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards which do not result in classification	Combustible.
Supplemental information	4.8% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 4.8% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixture

Identity of chemical ingredients	CAS number and other unique identifiers	Concentration of ingredients
Heptane	142-82-5	50 - < 60
Hydrotreated Light Distillates (petroleum)	64742-47-8	30 - < 40
Silicone Oil	63148-62-9	5 - < 10
Other components below reportable levels		3 - < 5

4. First-aid measures

Description of necessary first aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Personal protection for first-aid responders	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
Symptoms caused by exposure	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Diarrhea. Irritation of eyes and mucous membranes. Irritation of nose and throat. Skin irritation. May cause redness and pain.
Medical attention and special treatment	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for fire fighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Hazchem code None.

General fire hazards Extremely flammable aerosol. Combustible.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

For emergency responders Not available.

Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Precautions for safe handling Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls and personal protection

Control parameters Follow standard monitoring procedures.

Occupational exposure limits

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)

Components	Type	Value
Heptane (CAS 142-82-5)	STEL	2050 mg/m ³
		500 ppm
	TWA	1640 mg/m ³
		400 ppm

Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)

Components	Type	Value
Heptane (CAS 142-82-5)	STEL	2050 mg/m ³
		500 ppm
	TWA	1640 mg/m ³
		400 ppm

ACGIH Components	Type	Value	Form
Hydrotreated Light Distillates (petroleum) (CAS 64742-47-8)	TWA	200 mg/m ³	As Total Hydrocarbon Vapor.
US. ACGIH Threshold Limit Values Components	Type	Value	
Heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
UK. EH40 Workplace Exposure Limits (WELs) Components	Type	Value	
Heptane (CAS 142-82-5)	TWA	2085 mg/m ³ 500 ppm	
Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)			
Components	Type	Value	Form
Heptane (CAS 142-82-5)	TWA	2100 mg/m ³ 500 ppm	
Hydrotreated Light Distillates (petroleum) (CAS 64742-47-8)	TWA	5 mg/m ³	Respirable aerosol fraction
		350 mg/m ³ 50 ppm	Vapor. Vapor.

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.
Individual protection measures, for example personal protective equipment (PPE)	
Eye/face protection	Chemical respirator with organic vapor cartridge and full facepiece.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-131.08 °F (-90.6 °C) estimated
Initial boiling point and boiling range	Not available.
Flash point	24.8 °F (-4.0 °C)
Evaporation rate	Not available.

Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Density	544.00 kg/m ³
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Negligible
Solubility (other)	Oil
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	326 cSt ASTM D445
Viscosity temperature	104 °F (40 °C)
Other physical and chemical parameters	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.54

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Irritants. At thermal decomposition temperatures, carbon monoxide and carbon dioxide.

11. Toxicological information

Information on possible routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to exposure	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Diarrhea. Irritation of eyes and mucous membranes. Irritation of nose and throat. Skin irritation. May cause redness and pain.
Acute toxicity	Narcotic effects.

Product	Species	Test Results
No-Tox Food Grade Silicone Lubricant		
Acute		
Inhalation		
LC50	Rat	178 mg/l, 4 Hours estimated
LD50	Mouse	129 mg/l, 2 Hours estimated

Product	Species	Test Results
Oral		
LD50	Guinea pig	17571 g/kg estimated
	Mouse	71429 g/kg estimated
	Rabbit	17723 g/kg estimated
	Rat	41714 g/kg estimated
Components	Species	Test Results
Heptane (CAS 142-82-5)		
Acute		
Inhalation		
LC50	Rat	103 mg/l, 4 Hours
LD50	Mouse	75 mg/l, 2 Hours

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Due to lack of data the classification is not possible.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Due to lack of data the classification is not possible.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	Very toxic to aquatic life with long lasting effects.		
Components	Species	Test Results	
Heptane (CAS 142-82-5)			
Aquatic			
Fish	LC50	Mozambique tilapia (<i>Tilapia mossambica</i>)	375 mg/l, 96 hours
Silicone Oil (CAS 63148-62-9)			
Aquatic			
Fish	LC50	Channel catfish (<i>Ictalurus punctatus</i>)	2.36 - 4.15 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	
Partition coefficient n-octanol / water (log Kow)	
Heptane	4.66
Mobility in soil	This product is miscible in water.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal methods	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

ADG

UN number	1950
UN proper shipping name	Aerosol
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	Yes
Hazchem code	2T
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

UN number	1950
UN proper shipping name	AEROSOLS, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number	1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	1950
UN proper shipping name	AEROSOLS, flammable, MARINE POLLUTANT
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.

Environmental hazards

Marine pollutant

yes

EmS

Not available.

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.


ADG



IATA; IMDG; RID



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

Safety, health and environmental regulations

National regulations

This Safety Data Sheet was prepared in accordance with Australia Model Code of Practice for the preparation of Safety Data Sheets for Hazardous Chemicals (23/12/2011).

Australia Medicines & Poisons Appendix E

Heptane (CAS 142-82-5)

For advice, contact a Poisons information Centre (Phone eg Australia 131 - 126; New Zealand 03 - 4747 - 000) or a doctor (at once)., If swallowed, do NOT induce vomiting.

Australia Medicines & Poisons Schedule 5

Heptane (CAS 142-82-5)

applies to all preparations in any concentration Exception may apply, see the regulation for relevance.

Hydrotreated Light Distillates (petroleum) (CAS 64742-47-8)

applies to all preparations in any concentration Exception may apply, see the regulation for relevance.

High Volume Industrial Chemicals (HVIC)

Hydrotreated Light Distillates (petroleum) (CAS 64742-47-8)

1000 - 9999 TONNES See the regulation for additional information.

International regulations

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no) *
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 12-07-2016

Revision date 07-10-2018

Disclaimer Calumet Branded Products, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available