Issue date: 11-14-2017 Revision date: 09-19-2018 Supersedes date: 11-14-2017 Version number: 2.0



SAFETY DATA SHEET

1. Identification

Product identifier Raylene Extreme Pressure Oil 320

Product Code 301089

Other means of identification

Old Product Code 71630; For Package Codes 301089XXXXXX **Synonyms**

Product Code 301089

Recommended use of the chemical and restrictions on use

Recommended use Lubricant Not available. Restrictions on use

Details of manufacturer or importer

Calumet Branded Products, LLC

GPO Darling Park Towers 2 201 Sussex St. Sydney AU NSW 2000 Australia

2780 Waterfront Pkwy E. Dr., Suite 200 Indianapolis, IN 46214

1 317 328 5660

CHEMTREC: 1800 069 100 (AUS)

2. Hazard(s) identification

Classification of the hazardous chemical

Physical hazards Not classified. **Health hazards** Not classified. **Environmental hazards** Not classified.

Label elements, including precautionary statements

Hazard symbol(s) None Signal word None.

Hazard statement(s) The mixture does not meet the criteria for classification.

Precautionary statement(s)

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Other hazards which do not

result in classification

None known.

Supplemental information 98.36% of the mixture consists of component(s) of unknown acute dermal toxicity. 98.36% of the

mixture consists of component(s) of unknown acute inhalation toxicity. 88.57% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 88.57% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mivturo

Identity of chemical ingredients	CAS number and other unique identifiers	Concentration of ingredients
PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED HEAVY	64742-70-7	80 - < 90
Distillates (petroleum), Solvent-dewaxed Heavy Paraffinic	64742-65-0	5 - < 10
Distillates (petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	1 - < 3
Other components below reportable levels		5 - < 10

Material name: Raylene Extreme Pressure Oil 320

SDS AUSTRALIA 301089 Version #: 2.0 Revision date: 09-19-2018 Print date: 09-19-2018

4. First-aid measures

Description of necessary first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Personal protection for first-aid responders

Not available.

Symptoms caused by

Irritation of eyes and mucous membranes. Skin irritation.

exposure

Medical attention and special Treat symptomatically.

treatment

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

Water fog.

media

media

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for fire

fighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Wear

suitable protective equipment.

Hazchem code None

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate

protective clothing. For personal protection, see section 8 of the SDS.

For emergency responders

Not available.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

Methods and materials for containment and cleaning up The product is immiscible with water and will spread on the water surface. Prevent entry into

waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Precautions for safe handling

Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls and personal protection

Control parameters Follow standard monitoring procedures.

Material name: Raylene Extreme Pressure Oil 320

SDS AUSTRALIA

Occupational exposure limits

Australia. National Workplace OELs	s (Workplace Expo	sure Standards for Airborne Contaminants, Appendix A)
Components	Type	Value

Components	Туре	Value	
Distillates (petroleum), Hydrotreated Heavy Paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	
Distillates (petroleum), Solvent-dewaxed Heavy Paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	
PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED HEAVY (CAS 64742-70-7)	TWA	5 mg/m3	

Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)

Components	Туре	Value	Form	
Distillates (petroleum), Hydrotreated Heavy Paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Mist.	
Distillates (petroleum), Solvent-dewaxed Heavy Paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Mist.	
PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED HEAVY (CAS 64742-70-7)	TWA	5 mg/m3	Mist.	

US. ACGIH Threshold Limit Values

Туре	Value	Form
TWA	5 mg/m3	Inhalable fraction.
		.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,

DEWAXED HEAVY (CAS 64742-70-7)

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Туре	Value	Form
Distillates (petroleum), Hydrotreated Heavy Paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Respirable fraction.
Distillates (petroleum), Solvent-dewaxed Heavy Paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Respirable fraction.
PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED HEAVY (CAS 64742-70-7)	TWA	5 mg/m3	Respirable fraction.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, for example personal protective equipment (PPE)

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Material name: Raylene Extreme Pressure Oil 320
301089 Version #: 2.0 Revision date: 09-19-2018 Print date: 09-19-2018

SDS AUSTRALIA

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Always observe good personal hygiene measures, such as washing after handling the material and Hygiene measures

before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid.

Color Not available. Odor Not available. **Odor threshold** Not available. Not available. Melting point/freezing point Not available.

Initial boiling point and

boiling range

> 644 °F (> 340 °C)

Flash point 374.0 °F (190.0 °C) Pensky-Martens Closed Cup

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits Not available.

Flammability limit - lower

(%)

Flammability limit upper (%)

(%)

Not available. **Explosive limit - lower**

Explosive limit - upper

(%)

Not available.

Not available.

0.000002 hPa estimated Vapor pressure

Density 918.00 kg/m3 Vapor density Not available. Not available. Relative density

Solubility(ies)

Insoluble Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature 500 °F (260 °C) estimated

Decomposition temperature Not available. **Viscosity** 320 cSt

104 °F (40 °C) Viscosity temperature

Other physical and chemical parameters **Explosive properties** Not explosive.

Oxidizing properties Not oxidizing. Percent volatile 0.00009 % estimated

Specific gravity 0.92 VOC 0 %

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous No dangerous reaction known under conditions of normal use.

reactions

301089 Version #: 2.0 Revision date: 09-19-2018 Print date: 09-19-2018

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Strong oxidizing agents.

Incompatible materials

Hazardous decomposition

products

At thermal decomposition temperatures, carbon monoxide and carbon dioxide.

11. Toxicological information

Information on possible routes of exposure

InhalationNo adverse effects due to inhalation are expected.Skin contactNo adverse effects due to skin contact are expected.Eye contactDirect contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to

exposure

Irritation of eyes and mucous membranes. Skin irritation.

Acute toxicity Not known.

Skin corrosion/irritationDue to partial or complete lack of data the classification is not possible.

Serious eye Direct contact with eyes may cause temporary irritation.

damage/irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Based on available data, the classification criteria are not met.

ACGIH Carcinogens

Distillates (petroleum), Hydrotreated Heavy Paraffinic A4 Not classifiable as a human carcinogen.

(CAS 64742-54-7)

Distillates (petroleum), Solvent-dewaxed Heavy Paraffinic A4 Not classifiable as a human carcinogen.

(CAS 64742-65-0)

PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED

A2 Suspected human carcinogen.

HEAVY (CAS 64742-70-7)

A4 Not classifiable as a human carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Due to lack of data the classification is not possible.

Aspiration hazardNot an aspiration hazard.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

No data is available on the degradability of any ingredients in the mixture.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal methodsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Material name: Raylene Extreme Pressure Oil 320

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

ADG

Not regulated as dangerous goods.

RID

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

Safety, health and environmental regulations

National regulations This Safety Data Sheet was prepared in accordance with Australia Model Code of Practice for the

preparation of Safety Data Sheets for Hazardous Chemicals (23/12/2011).

High Volume Industrial Chemicals (HVIC)

Distillates (petroleum), Hydrotreated Heavy Paraffinic

1000 - 9999 TONNES See the regulation for additional information.

On inventory (yes/no)*

(CAS 64742-54-7)

Distillates (petroleum), Solvent-dewaxed Heavy Paraffinic 10000 - 99999 TONNES See the regulation for additional information.

Australian Inventory of Chemical Substances (AICS)

(CAS 64742-65-0)

International regulations

Australia

International Inventories		
Country(s) or region	Inventory name	

	, ,	
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*Δ "Ves" indicates that all compo	nents of this product comply with the inventory requirements administered by the governing country(s)	

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 11-14-2017 **Revision date** 09-19-2018

Disclaimer Calumet Branded Products, LLC cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in

the sheet was written based on the best knowledge and experience currently available.

This document has undergone significant changes and should be reviewed in its entirety **Revision information**

Material name: Raylene Extreme Pressure Oil 320 301089 Version #: 2.0 Revision date: 09-19-2018 Print date: 09-19-2018