Version number: 5.0



SAFETY DATA SHEET

1. Identification

Product identifier Termalene EP Grease LC 000

Product Code 301086 SDS number 7286

Other means of identification

Synonyms Old Product Code 70316; For Package Codes 301086XXXXXX

Product Code 301086

Recommended use of the chemical and restrictions on use

Recommended use Multipurpose Grease

Restrictions on use Not available.

Details of manufacturer or importer

Calumet Branded Products, LLC

GPO Darling Park Towers 2 201 Sussex St. Sydney AU NSW 2000 Australia

2780 Waterfront Pkwy E. Dr., Suite 200 Indianapolis, IN 46214

1 317 328 5660

CHEMTREC: 1800 069 100 (AUS)

2. Hazard(s) identification

Classification of the hazardous chemical

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.

Label elements, including precautionary statements

Hazard symbol(s) None.
Signal word None.

Hazard statement(s) The mixture does not meet the criteria for classification.

Precautionary statement(s)

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Other hazards which do not

result in classification

None known.

Supplemental information 99.1% of the mixture consists of component(s) of unknown acute oral toxicity. 99.1% of the

mixture consists of component(s) of unknown acute dermal toxicity. 99.1% of the mixture consists of component(s) of unknown acute inhalation toxicity. 17.84% of the mixture consists of

component(s) of unknown acute hazards to the aquatic environment.

3. Composition/information on ingredients

Mixture

Identity of chemical ingredients	CAS number and other unique identifiers	Concentration of ingredients
HYDROTREATED HEAVY NAPHTHENIC DISTILLATE (PETROLEUM)	64742-52-5	40 - < 50
Distillates (petroleum), Solvent-dewaxed Heavy Paraffinic	64742-65-0	30 - < 40
Distillates (petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	5 - < 10

Material name: Termalene EP Grease LC 000 SDS AUSTRALIA

301086 Version #: 5.0 Revision date: 09-20-2018 Print date: 09-20-2018

Residual Oils (petroleum), Solvent-dewaxed	64742-62-7	5 - < 10
Other components below reportable levels		3 - < 5

4. First-aid measures

Description of necessary first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Treat symptomatically.

Personal protection for first-aid responders

Not available.

Symptoms caused by

exposure

Irritation of eyes and mucous membranes. Skin irritation.

Medical attention and special

treatment

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Water fog.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for fire

fighters

5 • • **5**

suitable protective equipment.

Hazchem code None

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Wear

protective clothing. For personal protection, see section 8 of the SDS.

For emergency responders

Not available.

Environmental precautions

Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up

Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Precautions for safe handling

Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls and personal protection

Control parameters Follow standard monitoring procedures.

Occupational exposure limits

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)
Components Value

Distillates (petroleum), Hydrotreated Heavy Paraffinic (CAS 64742-54-7) TWA 5 mg/m3

Material name: Termalene EP Grease LC 000
301086 Version #: 5.0 Revision date: 09-20-2018 Print date: 09-20-2018

SDS AUSTRALIA

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A) Components **Type** Value Distillates (petroleum), TWA 5 mg/m3 Solvent-dewaxed Heavy Paraffinic (CAS 64742-65-0) HYDROTREATED HEAVY TWA 5 mg/m3 NAPHTHENIC DISTILLATE (PETROLEUM) (CAS 64742-52-5) Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational **Environment) Form** Components **Type** Value Distillates (petroleum), TWA 5 mg/m3 Mist. Hydrotreated Heavy Paraffinic (CAS 64742-54-7) Distillates (petroleum), TWA Mist. 5 mg/m3 Solvent-dewaxed Heavy Paraffinic (CAS 64742-65-0) HYDROTREATED HEAVY TWA 5 mg/m3 Mist. NAPHTHENIC DISTILLATE (PETROLEUM) (CAS 64742-52-5) **ACGIH** Form Value Components **Type** Residual Oils (petroleum), **TWA** 5 mg/m3 Inhalable fraction. Solvent-dewaxed (CAS 64742-62-7) **US. ACGIH Threshold Limit Values** Components Value Form **Type** HYDROTREATED HEAVY **TWA** 5 mg/m3 Inhalable fraction. NAPHTHENIC DISTILLATE (PETROLEUM) (CAS 64742-52-5) Residual Oils (petroleum), TWA 5 mg/m3 Inhalable fraction. Solvent-dewaxed (CAS 64742-62-7) Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Value Form Type Distillates (petroleum), TWA 5 mg/m3 Respirable fraction. Hydrotreated Heavy Paraffinic (CAS 64742-54-7) Distillates (petroleum), **TWA** 5 mg/m3 Respirable fraction. Solvent-dewaxed Heavy Paraffinic (CAS 64742-65-0) HYDROTREATED HEAVY TWA 5 mg/m3 Respirable fraction. NAPHTHENIC DISTILLATE (PETROLEUM) (CAS

Biological limit values No biological exposure limits noted for the ingredient(s).

TWA

Exposure guidelinesOccupational Exposure Limits are not relevant to the current physical form of the product.

5 mg/m3

Material name: Termalene EP Grease LC 000

64742-52-5)

64742-62-7)

Residual Oils (petroleum),

Solvent-dewaxed (CAS

SDS AUSTRALIA

Respirable fraction.

301086 Version #: 5.0 Revision date: 09-20-2018 Print date: 09-20-2018

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure

limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, for example personal protective equipment (PPE)

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Always observe good personal hygiene measures, such as washing after handling the material and Hygiene measures

before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Not available. Liquid. Paste. Form Color Not available. Not available. Odor **Odor threshold** Not available. Not available. Melting point/freezing point Not available.

Initial boiling point and

boiling range

680 °F (360 °C) estimated

Flash point 302.0 °F (150.0 °C) Pensky-Martens Closed Cup estimated

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure Not available. **Density** 0.86 g/cm3 Not available. Vapor density Relative density Not available.

Solubility(ies)

Not available. Solubility (water)

Solubility (other) Oil

Not available. **Partition coefficient**

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Viscosity Not available. Other physical and chemical parameters

Material name: Termalene EP Grease LC 000

Explosive properties Not explosive.

SDS AUSTRALIA

Kinematic viscosity 150 cSt Base Oil Oxidizing properties Not oxidizing. Percent volatile 0.01 % estimated

Specific gravity 0.86

VOC 0.01 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

At thermal decomposition temperatures, carbon monoxide and carbon dioxide.

11. Toxicological information

Information on possible routes of exposure

Inhalation No adverse effects due to inhalation are expected. Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to

exposure

Irritation of eyes and mucous membranes. Skin irritation.

Acute toxicity Not known.

Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible.

Serious eye Direct contact with eyes may cause temporary irritation.

damage/irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization. Based on available data, the classification criteria are not met. Germ cell mutagenicity Carcinogenicity Based on available data, the classification criteria are not met.

ACGIH Carcinogens

Distillates (petroleum), Hydrotreated Heavy Paraffinic A4 Not classifiable as a human carcinogen.

(CAS 64742-54-7)

Distillates (petroleum), Solvent-dewaxed Heavy Paraffinic A4 Not classifiable as a human carcinogen.

(CAS 64742-65-0)

HYDROTREATED HEAVY NAPHTHENIC DISTILLATE A2 Suspected human carcinogen.

(PETROLEUM) (CAS 64742-52-5)

A4 Not classifiable as a human carcinogen.

Residual Oils (petroleum), Solvent-dewaxed (CAS A2 Suspected human carcinogen.

64742-62-7)

A4 Not classifiable as a human carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Due to lack of data the classification is not possible.

Aspiration hazard Based on available data, the classification criteria are not met.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment. Material name: Termalene EP Grease LC 000

Product Species Test Results

Termalene EP Grease LC 000

Aquatic

Fish LC50 Fish 238.9308 mg/l, 96 hours estimated

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil No data available for this product.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal methodsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

ADG

Not regulated as dangerous goods.

RID

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

Safety, health and environmental regulations

National regulations This Safety Data Sheet was prepared in accordance with Australia Model Code of Practice for the

preparation of Safety Data Sheets for Hazardous Chemicals (23/12/2011).

High Volume Industrial Chemicals (HVIC)

Distillates (petroleum), Hydrotreated Heavy Paraffinic

1000 - 9999 TONNES See the regulation for additional information.

(CAS 64742-54-7)

Distillates (petroleum), Solvent-dewaxed Heavy Paraffinic 10000 - 99999 TONNES See the regulation for additional

(CAS 64742-65-0) information.

Residual Oils (petroleum), Solvent-dewaxed (CAS 1000 - 9999 TONNES See the regulation for additional information.

64742-62-7)

International regulations

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No

Country(s) or region On inventory (yes/no)* **Inventory name** New Zealand **New Zealand Inventory Philippines** Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI) Taiwan No United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

16. Other information

Issue date 10-28-2016 **Revision date** 09-20-2018

Disclaimer Calumet Branded Products, LLC cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in

the sheet was written based on the best knowledge and experience currently available.

Revision information This document has undergone significant changes and should be reviewed in its entirety

Material name: Termalene EP Grease LC 000 SDS AUSTRALIA