Issue date: 06-01-2016 Revision date: 05-22-2019 Supersedes date: 07-03-2018 Version number: 7.0



SAFETY DATA SHEET

1. Identification

Product identifier No-Tox Food Grade Waterproof Chain Lubricant

Product Code 301248 SDS number 7297

Other means of identification

Synonyms Old product Code 64070; For Package Codes 301248XXXXXX

Product Code 301248

Recommended use of the chemical and restrictions on use

Recommended use Chain Lubricant Restrictions on use Not available.

Details of manufacturer or importer

Calumet Branded Products, LLC

GPO Darling Park Towers 2 201 Sussex St. Sydney AU NSW 2000 Australia

2780 Waterfront Pkwy E. Dr., Suite 200 Indianapolis, IN 46214

1 317 328 5660

CHEMTREC: 1800 069 100 (AUS)

2. Hazard(s) identification

Classification of the hazardous chemical

Physical hazardsFlammable aerosolsCategory 1Health hazardsSkin corrosion/irritationCategory 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

Category 2

exposure

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment,

long-term hazard

Category 2

Category 2

Label elements, including precautionary statements

Hazard symbol(s)



Flame Health hazard Exclamation Environment

Signal word Danger

Hazard statement(s) Extremely flammable aerosol. Causes skin irritation. May cause drowsiness or dizziness. May cause

damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic

life with long lasting effects.

Precautionary statement(s)

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do

not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves.

IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and Response

> keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated

clothing and wash before reuse. Collect spillage.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from Storage

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards which do not result in classification **Supplemental information**

Combustible.

99.2% of the mixture consists of component(s) of unknown acute oral toxicity. 99.2% of the mixture consists of component(s) of unknown acute dermal toxicity, 51,19% of the mixture consists of component(s) of unknown acute inhalation toxicity. 66.2% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 66.2% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 66.2% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. 66.2% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixture

Identity of chemical ingredients	CAS number and other unique identifiers	Concentration of ingredients
White Mineral Oil (petroleum)	8042-47-5	38 - < 39
Heptane	142-82-5	20
Hydrotreated Light Distillates (petroleum)	64742-47-8	10 - 15
Propane	74-98-6	8.63
Butane	106-97-8	6.38

4. First-aid measures

Description of necessary first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. Do Ingestion

not induce vomiting without advice from poison control center. If vomiting occurs, keep head low

so that stomach content doesn't get into the lungs.

Personal protection for first-aid responders

Symptoms caused by

exposure

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous membranes. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic

effects.

Medical attention and special

treatment

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).

media

Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire. media

Specific hazards arising from

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

the chemical During fire, gases hazardous to health may be formed. Special protective equipment and precautions for fire

fighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or

monitor nozzles, if possible. If not, withdraw and let fire burn out.

Hazchem code

General fire hazards

Specific methods

 ${\bf Extremely\ flammable\ aerosol.\ Combustible.}$

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

None

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS

For emergency responders

Not available.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent entry into waterways, sewer, basements or confined areas. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls and personal protection

Control parameters

Follow standard monitoring procedures.

Occupational exposure limits

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)
Components

Type

Value

TWA

1900 mg/m3
800 ppm

Australia. National Workplace Ol Components	Туре	Value	
Heptane (CAS 142-82-5)	STEL	2050 mg/m3	
		500 ppm	
	TWA	1640 mg/m3	
		400 ppm	
White Mineral Oil (petroleum) (CAS 8042-47-5)	TWA	5 mg/m3	
Australia. OELs. (Adopted Nation	nal Exposure Standards for I	Atmospheric Contaminants i	n the Occupational
Environment) Components	Туре	Value	Form
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Heptane (CAS 142-82-5)	STEL	2050 mg/m3	
•		500 ppm	
	TWA	1640 mg/m3	
		400 ppm	
White Mineral Oil (petroleum) (CAS 8042-47-5)	TWA	5 mg/m3	Mist.
ACGIH Components	Туре	Value	Form
Hydrotreated Light Distillates (petroleum) (CAS 64742-47-8)	TWA	200 mg/m3	As Total Hydrocarbor Vapor.
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	Form
Butane (CAS 106-97-8)	STEL	1000 ppm	
Heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
White Mineral Oil (petroleum) (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.
UK. EH40 Workplace Exposure L	imits (WELs)		
Components	Туре	Value	
Butane (CAS 106-97-8)	STEL	1810 mg/m3	
		750 ppm	
	TWA	1450 mg/m3	
		600 ppm	
		2085 mg/m3	
Heptane (CAS 142-82-5)	TWA	<u> </u>	
Heptane (CAS 142-82-5)	TWA	500 ppm	
Germany. DFG MAK List (advisor	ry OELs). Commission for the	500 ppm e Investigation of Health Ha	zards of Chemical
Germany. DFG MAK List (advisor Compounds in the Work Area (D	ry OELs). Commission for the		zards of Chemical Form
Germany. DFG MAK List (advisor Compounds in the Work Area (D Components	ry OELs). Commission for the FG) Type	e Investigation of Health Ha Value	
Germany. DFG MAK List (advisor Compounds in the Work Area (D Components	ry OELs). Commission for the	Value 2400 mg/m3	
Heptane (CAS 142-82-5) Germany. DFG MAK List (advisor Compounds in the Work Area (D Components Butane (CAS 106-97-8) Heptane (CAS 142-82-5)	ry OELs). Commission for the FG) Type	e Investigation of Health Ha Value	

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Туре	Value	Form
Hydrotreated Light Distillates (petroleum) (CAS 64742-47-8)	TWA	5 mg/m3	Respirable aerosol fraction
		350 mg/m3	Vapor.
		50 ppm	Vapor.
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
White Mineral Oil (petroleum) (CAS 8042-47-5)	TWA	5 mg/m3	Respirable fraction.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, for example personal protective equipment (PPE)

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

When using do not smoke. Always observe good personal hygiene measures, such as washing after Hygiene measures

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing

and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Aerosol Color Not available. Odor Not available. **Odor threshold** Not available. Not available. Melting point/freezing point Not available. Initial boiling point and Not available.

boiling range Flash point

-155.2 °F (-104.0 °C)

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

0.7 % estimated

(%)

Flammability limit -

9.5 % estimated

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Vapor pressureNot available.Density884.00 kg/m³Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Negligible
Solubility (other) Oil

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature

Decomposition temperature

Viscosity

Not available.

Not available.

Not available.

Other physical and chemical parameters

Explosive properties Not explosive.

Flash point class Flammable IA

Oxidizing properties Not oxidizing.

Specific gravity 0.88 VOC 35 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials

Hazardous decomposition

products

Strong oxidizing agents. Chlorine. Fluorine. Nitrates.

Irritants. At thermal decomposition temperatures, carbon monoxide and carbon dioxide.

11. Toxicological information

Information on possible routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to

exposure

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous

membranes. Skin irritation. May cause redness and pain.

Acute toxicity Not known.

Components Species Test Results

Heptane (CAS 142-82-5)

Acute Inhalation

LC50 Rat 103 mg/l, 4 Hours

Skin corrosion/irritation Causes skin irritation.

Serious eye Direct contact with eyes may cause temporary irritation.

damage/irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Not applicable.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

ACGIH Carcinogens

White Mineral Oil (petroleum) (CAS 8042-47-5)

A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

White Mineral Oil (petroleum) (CAS 8042-47-5)

3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity May cause drowsiness and dizziness.

- single exposure

Specific target organ toxicity - repeated exposure

Aspiration hazard Based on available data, the classification criteria are not met.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may

May cause damage to organs through prolonged or repeated exposure.

be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Product Species Test Results No-Tox Food Grade Waterproof Chain Lubricant **Aquatic** Crustacea FC50 Daphnia 540.0812 mg/l, 48 hours estimated Fish LC50 Fish 11455.999 mg/l, 96 hours estimated Components **Species Test Results**

Heptane (CAS 142-82-5)

Aquatic

Fish LC50 Mozambique tilapia (Tilapia mossambica) 375 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log

Kow)

Butane 2.89
Heptane 4.66
Propane 2.36

Mobility in soil This product is miscible in water.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal methodsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under

pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Residual wasteDispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

ADG

UN number 1950

UN proper shipping name aerosol, flammable

Material name: No-Tox Food Grade Waterproof Chain Lubricant 301248 Version #: 7.0 Revision date: 05-22-2019 Print date: 05-22-2019

7 / 10

Transport hazard class(es)

Class 2.1 Subsidiary risk

Not available. Packing group **Environmental hazards** Not available.

Hazchem code 2YE

Special precautions for Read safety instructions, SDS and emergency procedures before handling.

user

RID

UN number 1950 **UN** proper shipping name **AEROSOLS**

Transport hazard class(es) Class 2.1 Subsidiary risk Label(s) 2.2 + 6.1Packing group Not available.

Environmental hazards

Special precautions for Read safety instructions, SDS and emergency procedures before handling.

user IATA

> **UN number** 1950

Aerosols, flammable **UN proper shipping name**

Transport hazard class(es)

Class 2.1 Subsidiary risk

Not available. Packing group

Environmental hazards No. **ERG Code** 10L

Special precautions for

user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo Forbidden

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number

UN proper shipping name Aerosols, Flammable

Transport hazard class(es) Class 2.1 Subsidiary risk

Packing group Not available.

Environmental hazards

Marine pollutant No. F-D, S-U **EmS**

Special precautions for

Read safety instructions, SDS and emergency procedures before handling.

Annex II of MARPOL 73/78

and the IBC Code

Transport in bulk according to Not established.

ADG



IATA; IMDG; RID



15. Regulatory information

Safety, health and environmental regulations

National regulations

This Safety Data Sheet was prepared in accordance with Australia Model Code of Practice for the preparation of Safety Data Sheets for Hazardous Chemicals (23/12/2011).

Australia Medicines & Poisons Appendix E

Butane (CAS 106-97-8)

Heptane (CAS 142-82-5)

White Mineral Oil (petroleum) (CAS 8042-47-5)

Australia Medicines & Poisons Schedule 5

Butane (CAS 106-97-8)

Heptane (CAS 142-82-5)

Hydrotreated Light Distillates (petroleum) (CAS 64742-47-8)

White Mineral Oil (petroleum) (CAS 8042-47-5)

High Volume Industrial Chemicals (HVIC)

Butane (CAS 106-97-8) 100000 - 999999 TONNES See the regulation for additional

information.

Hydrotreated Light Distillates (petroleum) (CAS 1000 - 9999 TONNES See the regulation for additional information.

64742-47-8)

Propane (CAS 74-98-6) 100000 - 999999 TONNES See the regulation for additional

information.

White Mineral Oil (petroleum) (CAS 8042-47-5) 1000 - 9999 TONNES See the regulation for additional information.

International regulations

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

Country(s) or region Inventory name On inventory (yes/no)*

Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI) No

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

 Issue date
 06-01-2016

 Revision date
 05-22-2019

Disclaimer Calumet Branded Products, LLC cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in

the sheet was written based on the best knowledge and experience currently available.

Revision information This document has undergone significant changes and should be reviewed in its entirety.