SAFETY DATA SHEET

Molylube Extreme Pressure Grease AC 1



Section 1. Identification

Product identifier : Molylube Extreme Pressure Grease AC 1

Product code : 301201150004

Other means of : Not available.
identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Not available.	
Uses advised against	Reason

Company name Calumet Branded Products, LLC

Address 2780 Waterfront Pkwy E. Dr., Suite 200

Indianapolis, IN 46214 USA

Technical Services 317-328-5660

24 hr CHEMTREC 1-800-424-9300/ International 1-703-527-3887

Importer Statewide Bearings

67 Kewdale Rd, Kewdale WA 6105 PO Box 205, WELSHPOOL DC WA 6986

Technical Services (During Normal Business Hours): (08) 9248 2381

24 hr. CHEMTREC Australia: +(61)-290372994

Section 2. Hazard(s) identification

Classification of the substance or mixture

: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITISATION - Category 1

SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 7.7%

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal

toxicity: 7.7%

Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation

toxicity: 10.2%

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 6.7%

GHS label elements

Hazard pictograms :



Signal word : WARNING

Hazard statements : Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

Precautionary statements

Date of issue/Date of revision : 06/01/2020 Version : 1 1/11

Section 2. Hazard(s) identification

Prevention

: Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapour. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Response

: IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage

: Not applicable.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label

elements

: Not applicable.

Other hazards which do not : None known.

result in classification

Section 3. Composition and ingredient information

Substance/mixture Other means of identification

: Mixture : Not available.

Ingredient name	% (w/w)	CAS number
Distillates (petroleum), hydrotreated heavy naphthenic	≥30 - ≤60	64742-52-5
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≥10 - ≤30	64742-65-0
Distillates (petroleum), hydrotreated heavy paraffinic	≥10 - ≤30	64742-54-7
White mineral oil (petroleum)	≤5	8042-47-5
5,5'-dithiodi-1,3,4-thiadiazole-2(3H)-thione	≤3	72676-55-2
molybdenum disulphide	≤3	1317-33-5
1H-Imidazole-1-ethanol, 4,5-dihydro-, 2-nortall-oil alkyl derivs.	≤2	61791-39-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date of revision : 06/01/2020 Version : 1

Section 4. First aid measures

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: Do not use water jet.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides

Date of issue/Date of revision : 06/01/2020 Version : 1 3/11

Section 5. Firefighting measures

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Date of issue/Date of revision : 06/01/2020 Version

Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls and personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy naphthenic	Safe Work Australia (Australia, 4/2018). TWA: 5 mg/m³ 8 hours. Form: Mist
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Safe Work Australia (Australia, 4/2018). TWA: 5 mg/m ³ 8 hours. Form: Mist
Distillates (petroleum), hydrotreated heavy paraffinic	Safe Work Australia (Australia, 4/2018). TWA: 5 mg/m³ 8 hours. Form: Mist
White mineral oil (petroleum)	Safe Work Australia (Australia, 4/2018). TWA: 5 mg/m³ 8 hours. Form: Mist
molybdenum disulphide	Safe Work Australia (Australia, 4/2018). TWA: 10 mg/m³, (as Mo) 8 hours.

Appropriate engineering controls

Environmental exposure controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date of revision : 06/01/2020 Version : 1

Section 8. Exposure controls and personal protection

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. [Viscous mass. Paste.]

Colour : Black.

Odour : Hydrocarbon. **Odour threshold** : Not available. : Not available. **Melting point** : Not available. : Not available. **Boiling point** Flash point : Not available. : Not available. **Evaporation rate** : Not available. Flammability (solid, gas) : Not available.

Lower and upper explosive

(flammable) limits

: Not available. Vapour pressure Vapour density : Not available.

Relative density : 0.8975 : Not available. Solubility Solubility in water : Not available. Partition coefficient: n-: Not available.

octanol/water

Auto-ignition temperature : Not available. **Decomposition temperature** : Not available. **Viscosity** : Not available. Flow time (ISO 2431) : Not available.

Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

: The product is stable. **Chemical stability**

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date of revision : 06/01/2020 Version 6/11

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	LC50 Inhalation Dusts and mists	Rat	5.7 mg/l	4 hours
·	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum),	LC50 Inhalation Dusts and mists	Rat	>5.53 mg/l	4 hours
solvent-dewaxed heavy				
paraffinic				
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum),	LC50 Inhalation Dusts and mists	Rat	5.7 mg/l	4 hours
hydrotreated heavy paraffinic				
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
White mineral oil (petroleum)	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
5,5'-dithiodi-	LD50 Dermal	Rabbit	>2000 mg/kg	-
1,3,4-thiadiazole-2(3H)-				
thione				
	LD50 Oral	Rat	>2000 mg/kg	-

Irritation/Corrosion

Not available.

Sensitisation

	Route of exposure	Species	Result
5,5'-dithiodi- 1,3,4-thiadiazole-2(3H)- thione	skin	Mouse	Sensitising

Mutagenicity

Product/ingredient name	Test	Experiment	Result
5,5'-dithiodi- 1,3,4-thiadiazole-2(3H)- thione	OECD 476 In vitro Mammalian Cell Gene Mutation Test	Experiment: In vitro Subject: Mammalian-Animal	Positive
	OECD 471 Bacterial Reverse Mutation Test	Experiment: In vitro Subject: Bacteria	Negative
	OECD 487 In vitro Micronucleus Test	Experiment: In vitro Subject: Mammalian-Animal	Negative

Carcinogenicity

Not available.

Reproductive toxicity

_	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
5,5'-dithiodi- 1,3,4-thiadiazole-2(3H)- thione	-	-	-		Oral: 300 mg/kg	47 days

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Date of issue/Date of revision : 06/01/2020 Version : 1 7/11

Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Name	Result
White mineral oil (petroleum)	ASPIRATION HAZARD - Category 1

Information on likely routes

of exposure

: Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
5,5'-dithiodi- 1,3,4-thiadiazole-2(3H)- thione	Sub-acute NOAEL Oral	Rat	1000 mg/kg	14 days

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Date of issue/Date of revision : 06/01/2020 Version :1 8/11

Section 11. Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	(gases)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Distillates (petroleum), hydrotreated heavy naphthenic Distillates (petroleum), hydrotreated heavy paraffinic	N/A N/A	N/A N/A		N/A N/A	5.7 5.7

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	Acute EC50 >100 mg/l	Algae	72 hours
•	Acute EC50 >100 mg/l	Crustaceans	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Acute EC50 >100 mg/l	Algae	72 hours
	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
	Chronic NOEL >1 mg/l	Daphnia	21 days
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute IC50 >100 mg/l	Algae	72 hours
	Acute LC50 >100 mg/l	Fish	96 hours
White mineral oil (petroleum)	Acute LC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >10000 mg/l	Fish	96 hours
5,5'-dithiodi-1,3,4-thiadiazole-2(3H)-thione	Acute EC10 9.4 mg/l	Algae	72 hours
,	Acute EC50 20 mg/l	Algae	72 hours
	Acute EC50 3 mg/l	Daphnia	48 hours
	Acute EC50 >454 mg/l	Fish	96 hours
1H-Imidazole-1-ethanol, 4,5-dihydro-, 2-nortall-oil alkyl derivs.	Acute EC50 1.7 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 1.07 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

Persistence and degradability

Product/ingredient name	Test	Result		Dose	Inoculum
5,5'-dithiodi-1,3,4-thiadiazole-2(3H)-thione	OECD 301B Ready Biodegradability - CO2 Evolution Test	0 % - Not readily - 28 days		-	-
Product/ingredient name	Aquatic half-life	Photolys		s	Biodegradability
Distillates (petroleum), hydrotreated heavy naphthenic	-		-		Inherent
Distillates (petroleum), hydrotreated heavy paraffinic	-		-		Not readily
White mineral oil (petroleum) 5,5'-dithiodi-1,3,4-thiadiazole-2(3H)-thione	-		-		Inherent Not readily

Date of issue/Date of revision : 06/01/2020 Version : 1 9/11

Molylube Extreme Pressure Grease AC 1

Section 12. Ecological information

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Distillates (petroleum), solvent-dewaxed heavy paraffinic	2 to 6	-	high
Distillates (petroleum), hydrotreated heavy paraffinic	>6	-	high
White mineral oil (petroleum) 1H-Imidazole-1-ethanol, 4,5-dihydro-, 2-nortall-oil alkyl derivs.	>6 5.4	-	high high

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	ADG	ADR/RID	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of Marpol and

the IBC Code

Section 15. Regulatory information

Standard Uniform Schedule of Medicine and Poisons

Not regulated.

Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

Inventory list

Australia : All components are listed or exempted. Canada All components are listed or exempted.

Date of issue/Date of revision : 06/01/2020 Version: 1 10/11

Section 15. Regulatory information

China : All components are listed or exempted.
 Europe : All components are listed or exempted.
 Japan inventory (ENCS): Not determined.
 Japan inventory (ISHL): Not determined.

: All components are listed or exempted.

Philippines : Not determined.

Republic of Korea : All components are listed or exempted.

Taiwan : All components are listed or exempted.

Thailand : Not determined.

Turkey : Not determined.

United States: All components are listed or exempted.

Viet Nam : Not determined.

Section 16. Any other relevant information

History

Date of issue/Date of : 06/01/2020

revision

New Zealand

Version : 1

Key to abbreviations : ADG = Australian Dangerous Goods

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group

SUSMP = Standard Uniform Schedule of Medicine and Poisons

UN = United Nations

Procedure used to derive the classification

Classification	Justification
SKIN IRRITATION - Category 2	Calculation method
EYE IRRITATION - Category 2A	Calculation method
SKIN SENSITISATION - Category 1	Calculation method
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3	Calculation method
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	Calculation method

[✓] Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 06/01/2020 Version : 1 11/11