# SAFETY DATA SHEET

Molylube SF 100 Semi-Synthetic Open Gear Lubricant Heavy



# Section 1. Identification

**Product identifier** : Molylube SF 100 Semi-Synthetic Open Gear Lubricant Heavy

300939150002 Product code Other means of : Not available.

identification

**Product type** : Liquid.

### Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Not available.	
Uses advised against	Reason

Calumet Branded Products, LLC -Company name **Address** 

2780 Waterfront Pkwy E. Dr., Suite 200

Indianapolis, IN 46214 USA

**Technical Services** 317-328-5660

24 hrCHEMTREC 1-800-424-9300/ International 1-703-527-3887

Statewide Bearings **Importer** 

> 67 Kewdale Rd, Kewdale WA 6105 PO Box 205, WELSHPOOL DC WA 6986

Technical Services (During Normal Business Hours): (08) 9248 2381

24 hr. CHEMTREC Australia: +(61)-290372994

# Section 2. Hazard(s) identification

Classification of the substance or mixture SKIN SENSITISATION - Category 1

SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 68.5%

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal

toxicity: 73.5% Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation

toxicity: 78.5%

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 67.5%

**GHS label elements** 

**Hazard pictograms** 



Signal word WARNING

**Hazard statements** May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention** : Wear protective gloves. Avoid release to the environment. Avoid breathing vapour.

Contaminated work clothing should not be allowed out of the workplace.

Response : IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing

before reuse. If skin irritation or rash occurs: Get medical attention.

**Storage** : Not applicable.

: 09/24/2020 Date of issue/Date of revision Version : 1 1/11 Molylube SF 100 Semi-Synthetic Open Gear Lubricant Heavy

# Section 2. Hazard(s) identification

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: Not applicable.

Other hazards which do not : None known.

# Section 3. Composition and ingredient information

Substance/mixture
Other means of
identification

: Mixture: Not available.

Ingredient name	% (w/w)	CAS number
Residual oils (petroleum), solvent-dewaxed	≥30 - ≤60	64742-62-7
Natural graphite	≥10 - ≤30	7782-42-5
Fatty acids, tallow, hydrogenated, reaction products with aluminum	≤10	68201-44-5
isopropoxide and benzoic acid		
carbon black	<10	1333-86-4
5,5'-dithiodi-1,3,4-thiadiazole-2(3H)-thione	≤3	72676-55-2
molybdenum disulphide	≤3	1317-33-5
Lubricating oils (petroleum), hydrotreated spent	≤3	64742-58-1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Date of issue/Date of revision : 09/24/2020 Version : 1 2/11

# Section 4. First aid measures

### Most important symptoms/effects, acute and delayed

## Potential acute health effects

**Eye contact**  No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards.

: May cause an allergic skin reaction. Skin contact

Ingestion : No known significant effects or critical hazards.

## Over-exposure signs/symptoms

**Eye contact** : No specific data. Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

> irritation redness

Ingestion : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** 

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear

### See toxicological information (Section 11)

# Section 5. Firefighting measures

### **Extinguishing media**

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: Do not use water jet.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being

discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

: 09/24/2020 Date of issue/Date of revision Version : 1 3/11

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

### For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

#### For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### **Environmental precautions**

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and material for containment and cleaning up

#### **Small spill**

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of issue/Date of revision : 09/24/2020 Version :1

# Section 8. Exposure controls and personal protection

#### **Control parameters**

### Occupational exposure limits

Ingredient name	Exposure limits
Residual oils (petroleum), solvent-dewaxed	Safe Work Australia (Australia, 4/2018). TWA: 5 mg/m³ 8 hours. Form: Mist
Natural graphite	Safe Work Australia (Australia, 4/2018). TWA: 3 mg/m³ 8 hours. Form: Respirable dust
Fatty acids, tallow, hydrogenated, reaction products with aluminum isopropoxide and benzoic acid	Safe Work Australia (Australia, 4/2018). TWA: 2 mg/m³, (as Al) 8 hours.
carbon black	Safe Work Australia (Australia, 4/2018). TWA: 3 mg/m³ 8 hours.
molybdenum disulphide	Safe Work Australia (Australia, 4/2018). TWA: 10 mg/m³, (as Mo) 8 hours.
Lubricating oils (petroleum), hydrotreated spent	ACGIH TLV (United States). TWA: 5 mg/m³, (Inhalable Mist) 8 hours.

# Appropriate engineering controls

**Environmental exposure** controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

# Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### **Respiratory protection**

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Date of issue/Date of revision : 09/24/2020 Version : 1 5/11

# Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid. [Viscous liquid. Paste.]

Colour : Black.

Odour : Not available.
Odour threshold : Not available.
pH : Not available.
Melting point : Not available.
Boiling point : 360°C (680°F)

Flash point : Closed cup: >260°C (>500°F) [Pensky-Martens.]

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapour pressure: Not available.Vapour density: Not available.

Relative density : 0.971

**Solubility** : Insoluble in the following materials: cold water and hot water.

Solubility in water : Not available.

Partition coefficient: n- : Not available.

octanol/water

**Auto-ignition temperature** : 260°C (500°F) **Decomposition temperature** : Not available.

Viscosity : Kinematic (40°C (104°F)): Not applicable.

Flow time (ISO 2431) : Not available.

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

# **Section 11. Toxicological information**

Information on toxicological effects

**Acute toxicity** 

Date of issue/Date of revision : 09/24/2020 Version : 1 6/11

# Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
Residual oils (petroleum), solvent-dewaxed	LC50 Inhalation Dusts and mists	Rat	>5.53 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
carbon black	LD50 Oral	Rat	>15400 mg/kg	-
5,5'-dithiodi-	LD50 Dermal	Rabbit	>2000 mg/kg	-
1,3,4-thiadiazole-2(3H)-				
thione				
	LD50 Oral	Rat	>2000 mg/kg	-
Lubricating oils (petroleum), hydrotreated spent	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

## **Irritation/Corrosion**

Not available.

### **Sensitisation**

3	Route of exposure	Species	Result
5,5'-dithiodi- 1,3,4-thiadiazole-2(3H)- thione	skin	Mouse	Sensitising

### **Mutagenicity**

Product/ingredient name	Test	Experiment	Result
5,5'-dithiodi- 1,3,4-thiadiazole-2(3H)- thione	OECD 476 In vitro Mammalian Cell Gene Mutation Test	Experiment: In vitro Subject: Mammalian-Animal	Positive
	OECD 471 Bacterial Reverse Mutation Test	Experiment: In vitro Subject: Bacteria	Negative
	OECD 487 In vitro Micronucleus Test	Experiment: In vitro Subject: Mammalian-Animal	Negative

## **Carcinogenicity**

Not available.

## **Reproductive toxicity**

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
5,5'-dithiodi- 1,3,4-thiadiazole-2(3H)- thione	-	-	-	Rat	Oral: 300 mg/kg	47 days

# **Teratogenicity**

Not available.

## Specific target organ toxicity (single exposure)

Not available.

## Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
carbon black	Category 2	Inhalation	Not determined

## **Aspiration hazard**

Not available.

Date of issue/Date of revision : 09/24/2020 Version : 1 7/11

# **Section 11. Toxicological information**

Information on likely routes : Not available.

of exposure

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards.

**Skin contact** : May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

: No specific data. **Eye contact** Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

> irritation redness

: No specific data. Ingestion

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

#### Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
5,5'-dithiodi- 1,3,4-thiadiazole-2(3H)- thione	Sub-acute NOAEL Oral	Rat	1000 mg/kg	14 days

**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. **Teratogenicity Developmental effects** : No known significant effects or critical hazards. **Fertility effects** : No known significant effects or critical hazards.

### **Numerical measures of toxicity**

**Acute toxicity estimates** 

N/A

Date of issue/Date of revision : 09/24/2020 Version :1 8/11

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Residual oils (petroleum), solvent-dewaxed	Acute EC50 >100 mg/l	Algae	72 hours
	Acute EC50 >100 mg/l	Crustaceans	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
carbon black	Acute EC50 37.563 mg/l Fresh water	Daphnia - Daphnia magna -	48 hours
		Neonate	
5,5'-dithiodi-1,3,4-thiadiazole-	Acute EC10 9.4 mg/l	Algae	72 hours
2(3H)-thione			
	Acute EC50 20 mg/l	Algae	72 hours
	Acute EC50 3 mg/l	Daphnia	48 hours
	Acute EC50 >454 mg/l	Fish	96 hours

### Persistence and degradability

Product/ingredient name	Test	Result		Dose	Inoculum
5,5'-dithiodi-1,3,4-thiadiazole-2(3H)-thione	OECD 301B Ready Biodegradability - CO2 Evolution Test	0 % - Not readily - 2	28 days	-	-
Product/ingredient name	Aquatic half-life		Photolysi	s	Biodegradability
Residual oils (petroleum), solvent-dewaxed 5,5'-dithiodi-1,3,4-thiadiazole-	-		-		Inherent  Not readily

# **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Residual oils (petroleum), solvent-dewaxed	>6	-	high

#### **Mobility in soil**

2(3H)-thione

Soil/water partition coefficient (Koc)

: Not available.

#### Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

## **Disposal methods**

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 09/24/2020 Version : 1 9/11

# **Section 14. Transport information**

	ADG	ADR/RID	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not available.

to Annex II of Marpol and

the IBC Code

# Section 15. Regulatory information

Standard Uniform Schedule of Medicine and Poisons

Not regulated.

Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

**Inventory list** 

**Australia** : Not determined.

Canada At least one component is not listed in DSL but all such components are listed in

China : All components are listed or exempted.

: Not determined. **Europe** 

: Japan inventory (ENCS): Not determined. **Japan** 

Japan inventory (ISHL): Not determined.

**New Zealand** : All components are listed or exempted. **Philippines** : All components are listed or exempted. **Republic of Korea** : All components are listed or exempted. **Taiwan** : All components are listed or exempted.

**Thailand** : Not determined. : Not determined. Turkey

**United States** : All components are listed or exempted.

**Viet Nam** : Not determined.

# Section 16. Any other relevant information

**History** 

Date of issue/Date of

revision

: 09/24/2020

Version : 1

Key to abbreviations : ADG = Australian Dangerous Goods

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

: 09/24/2020 Date of issue/Date of revision Version : 1 10/11

# Section 16. Any other relevant information

SGG = Segregation Group SUSMP = Standard Uniform Schedule of Medicine and Poisons UN = United Nations

### Procedure used to derive the classification

Classification	Justification
SKIN SENSITISATION - Category 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3	Calculation method Calculation method
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	Calculation method

<sup>▼</sup> Indicates information that has changed from previously issued version.

### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 09/24/2020 Version : 1 11/11