

Technical data

General	Lubrication and filling unit
Dimension	Size: 570 x 365 x 190 mm Weight: 10,5 kg
Power supply	Battery: Li-ion 48V/6Ah Charger: 50VDC/2A Ext.: 100-240VAC/50- 60Hz
Maximum Output Pressure	Cont.:200bar/2900psi Peak: 250bar/3625psi
Output Volume	500 ml/min 17 oz/min
Operation	Semi-automatic
Controller	Hove Electronic Controller Hove Smart Lube
Accuracy	+/- 1%



Datasheet **HOVE CARRY**

Hove Carry

Lubrication unit with high accuracy and high flow

Hove Carry is a portable lubrication pump for port cranes. With its compact design, battery-powered pump, and digital interface. Used with Hove Smart Lube gives you full mobility and easy tracking and documentation.

Advantages of Hove Carry pump:

√ Full mobility

Get an ergonomic, lightweight, and battery-powered pump that is easy to use in all spaces and conditions.

✓ A complete solution*

Ensure correct lubrication and complete documentation in one unified solution.

✓ Real-time tracking

Reduce paperwork and support analytical, data-driven maintenance with easy-to-pull data.

√ Reduced climate footprint

By minimizing lubricant consumption, you increase the bearing lifetime and reduce your CO2.



^{*}Used with Hove Smart Lube: https://hove-as.com/solutions/smart-lube/