





\sim 1	ICT	\sim $^{\prime}$			$\Gamma \wedge \Pi$	\circ
Uι	וכנ	Ul	VIER	DE	IAII	_0

OGOTOWIENDE	7 (120			
NAME:		CONTACT:		
ADDRESS:		PHONE:		
DATE:		FAX:		
Screw Jack type		,		
Translating Screw	☐ Rotating Screw	Upright	☐ Inverted	
Application require	ements			
Quantity required		Stroke (mm)		
Working load (N)		Tension	Compression	
Static load (N)		Tension		
Load Guidance:	Guided	Unguided	Compression	
	w: Off center distance	_	Side load (N)	
_	w. On center distance			
	<u></u> <u></u>	, , , , , , , , , , , , , , , , , , ,		
Duty cycle profile: (eg: ex	ctend, dwell 1min, retract, dwe	Il 1 min, 20 cycles per hr, 16h	nrs per day, 300 days per year)	
Screw Jack Features	S			
Mounting options				
Screw end:	Clevis	Thread	Top plate	
	Plain	Pilot	Other	
Extra options				
Anti Backlash	Anti-Rotation	Safety Nut	☐ Bottom Pipe	
Motorised	Limit Switches	Bellows	Other	
Speeds				
Application Environr	nent:			
Temperature Range:	°C		_°C	
Environmental conditior	1			
Livilorii ileritai coriattoi	1			
Drawings attached?	☐ Yes	☐ No		
Other Comments:				

NATIONAL LINEAR DEPARTMENT (WA)
VICTORIA - TASMANIA
NEW SOUTH WALES
QUEENSLAND
SOUTH AUSTRALIA - NT

linear@statewidebearings.com.au linearvic@statewidebearings.com.au linearnsw@statewidebearings.com.au linearqld@statewidebearings.com.au linearsa@statewidebearings.com.au

(08) 9475 5000 (03) 9755 6044 (02) 9616 0066 (07) 3717 4452 (08) 8260 7615